

Professional Studio Recording
Lead Vocals
Lead Instruments
Ensemble Recording
Professional Stage Miking

- AKG's legendary 1" edge-terminated large diaphragm sound
- Incredible 143dB dynamic range (up to 156 dB SPL)
- Switchable 20 dB attenuation pad and low cut switch
- Integrated capsule suspension to reduce mechanical noise
- Rugged double mesh grill for high RF immunity but unaffected acoustics
- Spider-type shock mount, windscreen and metal carrying case included
- All-metal die-cast body with shock- and scratch-resistant finish
- Designed, engineered and built in Vienna, Austria
- 3-year parts and labor warranty

C 214

Engineered Excellence built in Vienna, Austria.



AKG's legendary **C 414** needs no introduction – it is a tool found in most recording studios and has been used on **thousands of hit records**; it's been on stage with artists of **every musical genre** and is also used by **leading broadcast facilities** the world over.

The new **C 214** is designed as a cost-effective alternative to the high-end, industry-leading **C 414 family**. This new microphone uses **the same 1-inch dual-capsule as the legendary C 414** in a **single-diaphragm, cardioid-only** design. The result is a **class-leading performance** close to that of the famous **C414 B-XLS**.

The **C 214** has **AKG's legendary large-diaphragm sound** and is capable of **incredible 143 dB dynamic range** for uncompressed, life-like transients. The C 214's edge-terminated capsule delivers a **highly-detailed, up-front sound** that brings out every nuance of any voice or instrument. Thanks to its switchable **20-dB attenuation pad** and **low cut filter**, the C 214 can be used in sound fields **as high as 156 dB SPL** – so it can be used on stage for close-up miking for **even very loud applications** like drum overheads, guitar amps or high-output brass.

The C 214 features an **integrated capsule suspension** that reduces mechanical noise and resonances for **even greater sonic accuracy**. The **double mesh, all-metal grille** protects the capsule and ensures **high RF immunity** without affecting acoustical performance. The C 214 has a **roadworthy construction quality** with a modern **scratch-resistant** finish, a **dent-resistant**, metal grille and a gold-plated XLR-type output.

The **C 214** comes complete with **carrying case, windscreen**, and spider-type **shock mount**.

AKG SOUNDS BETTER



Professional Studio Recording

Lead Vocals

Lead Instruments

Ensemble Recording

Professional Stage Miking

Integrated suspension to reduce mechanical noise

Rugged double mesh grill for unaffected acoustics and high RF immunity

One Inch Large Diaphragm with patented Edge-Terminated Back-Plate Technology provides freely-vibrating membrane for a smooth and wide frequency response and high transient detail



Switchable 150 Hz, 6 dB/octave low cut filter reduces rumble and wind noise effectively



Switchable 20 dB Attenuation Pad for use in close-miking – up to 156 dB SPL

Well designed circuitry provides high sensitivity, maximum SPL capability and minimum noise

Gold-plated XLR-type output connector for loss-free signals

All-metal die-cast body with shock- and scratch-resistant finish




9 002761 021110



Specifications

| | |
|-------------------------------|---|
| Capsule | One Inch Large Diaphragm Condenser |
| Sensitivity | 20 mV/Pa (-34 dBV) |
| Frequency Range | 20 to 20,000 Hz |
| Equivalent noise level | 13 dB-A (IEC 60268-4) |
| Polar Pattern | Cardioid |
| Max. SPL | 136 / 156 dB SPL (0 / 20 dB Pad) |
| Dynamic range | 123 / 143 dB-A (0 / 20 dB Pad) |
| Low Cut Filter | 160 Hz, 6 dB/Octave, switchable |
| Attenuation Pad | 20 dB, switchable |
| Phantom Power | 12 to 52 V (IEC 61938) |
| Patents | AT 395.225, DE 4.103.784, JP 2.815.488 |
| Dimensions | 160 x 55 mm (6.3 x 2.2 in.) |
| Net / Shipping Weight | 280 / 1450 g (0.62 / 3.22 lbs) |
| Standard Accessories | H 85 Shock Mount, W 214 Windscreen, Metal Carrying Case |

Item number: C 214 3185Z0001



www.ake.com

AKG Acoustics GmbH

Lemböckgasse 21–25, 1230 Vienna / AUSTRIA, phone: + 43 1 86654 0
e-mail: sales@ake.com

AKG Acoustics, U.S.

8400 Balboa Boulevard, Northridge, CA 91329, U.S.A., phone: + 1 818 920 3212
e-mail: akeusa@harman.com

For other products and distributors worldwide visit www.ake.com
Specifications subject to change without notice.

H A Harman International Company

