



# AU-BT2-DA

## DANTE 2x1 CHANNEL BLUETOOTH ADAPTER

AU-BT2-DA from TiGHT AV allows for transmitting two channels of Bluetooth audio to your Dante network and simultaneously receiving one channel of Dante Audio. It supports sample rates up to 48kHz, using Audinate's original Dante Ultimo chip.

The AU-BT2-DA is a simple and cost-efficient solution to integrate wireless Bluetooth audio to and from a Dante network. Simply pair your device via the button on the adapter, and you are ready to play audio from your device or allow for migrating mobile calls to your Dante-enabled conference system.

PoE support allows for a simplified installation via a PoE-capable network switch or from a separate PoE injector.



## KEY FEATURES

- Plug and Play
- 2 x 1 audio channels with 24-bit audio support
- Bluetooth 5.0 support
- Maximum Bluetooth LoS transmission distance up to 20m
- Bluetooth pairing button on front
- Dante and AES67 support
- Supports 802.3af PoE
- Dante Controller and Dante Domain Manager compatible

## SPECIFICATIONS

### DANTE

Sample Rate:	48kHz
Bit Depth:	24
Dante Device Latency:	48V
Network Transport:	Dante Audio over IP AES67 RTP
Model Name:	AU-BT2-DA

### CONTROL

Control Part:	(1) Bluetooth pairing button
---------------	------------------------------

### GENERAL

Operation Temperature:	-5 to +55°
Storage Temperature:	-25 to +70°
Power:	802.3af PoE
Power Consumption:	1.9W (Max)
Dimensions (W x H x D):	115 x 34 x 28 mm
Net Weight:	70 g
Compliance:	FCC, CE
Environmental:	RoHs, WEEE

### PACKAGE LIST

1 x AU-BT2-DA  
1x User Manual



## TIGHT POLICY

**Faulty product - minimal down time.**

Up until six months after purchase, TiGHT AV will replace your product in advance of return of faulty product.

**Your investment - built to last.**

All TiGHT AV products come with a five year limited warranty.

